

AVIGILON™ AVA BULLET CAMERA

Avigilon Alta Cloud Security



Available in wide and telephoto lens options, the AI-powered Avigilon Ava Bullet Camera for Alta Aware provides flexible coverage to ensure security from any indoor or outdoor location. With up to 4K resolution, remote zoom and focus, HDR and IR illumination, the Bullet Camera provides crisp, clear images even in challenging lighting conditions. On-camera storage and processing and cloud management minimize physical infrastructure, enabling plug and play configuration for fast deployments. Intelligent video and audio analytics help detect threats in real-time, and provide valuable insights to improve operations.



Available in wide and tele lenses for flexible coverage




Built-in AI video and audio analytics and on-device storage



Simple to install with innovative sliding body design and easy onboarding



Factory-installed certificates backed by a trusted platform module (TPM)



Dynamic resolution up to 4K



NDA-compliant: designed and developed in Norway and the UK, manufactured in Taiwan

FEATURES

IMAGE SENSOR

8MP (4K) or 5MP

IMAGE SENSOR SIZE FORMAT

1/1.8"

LENS (WIDE)

Focal length: 4.3-10.8mm

Aperture: *f*/1.38-*f*/2.8

Zoom

IR illumination, max distance: 50m

Minimum illumination: 0.06 lux in color mode

LENS (TELE)

Focal length: 11-28mm

Aperture: *f*/1.47-*f*/1.69

Zoom

IR illumination, max distance: 90m

Minimum illumination: 0.06 lux in color mode

ZOOM

2.5x

IR NIGHT VISION

Automatic night mode

IR-cut filter

850 nm IR LED

FIELD OF VIEW (WIDE)

100° - 40° Horizontal, 53° - 23° Vertical

FIELD OF VIEW (TELE)

39° - 16° Horizontal, 23° - 9° Vertical

MAXIMUM RESOLUTION & FRAME RATE 8MP (4K)

3840x2160@30fps

MAXIMUM RESOLUTION & FRAME RATE 5MP (4K)

3072x1728@30fps

DYNAMIC RANGE

Multi-exposure line-based HDR

VIDEO COMPRESSION

H.264

Motion JPEG

AUDIO

Microphone array (4x microphones)

Audio classification

Audio localization

SECURITY

Trusted Platform Module (TPM 2.0)

Factory installed certificates

No default passwords

Mandatory access authentication

HTTPS/TLS encryption

NETWORK PROTOCOLS

IPv4, HTTPS, TLS, DNS, mDNS, DNS-SD, NTP, RTSP, RTP, RTCP, ICMP, DHCP, ARP

Streaming: RTP/UDP, RTP/RTSP/HTTPS/TCP

POWER SOURCE

PoE+ (802.3at Type 2), normal operation

PoE (802.3 af), without heat and IR

USB-C, installation only

POWER CONSUMPTION

Typical: 5 W

Max without heater, with IR: 13 W

Max with heater: 23 W

STORAGE

MicroSD

SDXC UHS-I

CONNECTION

802.3ab 10/100 Ethernet

USB-C for preview and setup

INSTALLATION AID

Versatile bracket, mounts to standard back boxes. Refer to technical drawing.

ADJUSTMENT RANGE

Pan, Tilt, Roll

IMPACT RESISTANCE

IK10 (IEC/EN 62262)

INGRESS PROTECTION

IP66 (IEC/EN 60529)

TEMPERATURE

Operating: -25°C to +50°C

Storage: -40°C to +60°C

PHYSICAL CHARACTERISTICS

Dimensions: 284x86x108

Weight: 1.33 kg

Body: Aluminum

EMC

EN55032, EN 61000-6-4, EN 61000-3-2, EN 61000-3-3, EN50130-4 CISPR 32, AS/NZS CISPR 32, FCC subpart 15B, ICES-003 Issue 7

SAFETY

UL (UL 62368-1)


CB (IEC/ EN 62368-1, IEC/EN 60950-22, IEC/EN 62471)

NOM-019


TECHNICAL DRAWINGS

Camera


Front view



Side view



Rear view



	DIMENSION (MM)	DIMENSION (INCH)	USAGE
A	42.3 x 71.2	1.67 x 2.8	Large fasteners & anchors
B	62.86 x 62.86 (88.9 diagonal)	2.47 x 2.47 (3.5 diagonal)	Ava Mounts, small fasteners



ORDERING INFORMATION

AVIGILON AVA BULLET TELE

PRODUCT ID	RESOLUTION	ONBOARD RETENTION	COLOR
BULLET-TE-W	4K	No. Cloud Connector required.	White
BULLET-TE-W-4K-30	4K	30 days	White
BULLET-TE-W-4K-60	4K	60 days	White
BULLET-TE-W-5MP	5MP	No. Cloud Connector required.	White
BULLET-TE-W-5MP-30	5MP	30 days	White
BULLET-TE-W-5MP-60	5MP	60 days	White
BULLET-TE-W-5MP-120	5MP	120 days	White
BULLET-TE-B	4K	No. Cloud Connector required.	Black
BULLET-TE-B-4K-30	4K	30 days	Black
BULLET-TE-B-4K-60	4K	60 days	Black
BULLET-TE-B-5MP	5MP	No. Cloud Connector required.	Black
BULLET-TE-B-5MP-30	5MP	30 days	Black
BULLET-TE-B-5MP-60	5MP	60 days	Black
BULLET-TE-B-5MP-120	5MP	120 days	Black



ORDERING INFORMATION

AVIGILON AVA BULLET WIDE

PRODUCT ID	RESOLUTION	ONBOARD RETENTION	COLOR
BULLET-WI-W	4K	No. Cloud Connector required.	White
BULLET-WI-W-4K-30	4K	30 days	White
BULLET-WI-W-4K-60	4K	60 days	White
BULLET-WI-W-5MP	5MP	No. Cloud Connector required.	White
BULLET-WI-W-5MP-30	5MP	30 days	White
BULLET-WI-W-5MP-60	5MP	60 days	White
BULLET-WI-W-5MP-120	5MP	120 days	White
BULLET-WI-B	4K	No. Cloud Connector required.	Black
BULLET-WI-B-4K-30	4K	30 days	Black
BULLET-WI-B-4K-60	4K	60 days	Black
BULLET-WI-B-5MP	5MP	No. Cloud Connector required.	Black
BULLET-WI-B-5MP-30	5MP	30 days	Black
BULLET-WI-B-5MP-60	5MP	60 days	Black
BULLET-WI-B-5MP-120	5MP	120 days	Black

ORDERING INFORMATION

ACCESSORIES

PRODUCT ID	PRODUCT NAME	COLOR
ACC-WEA-SHI-B	Avigilon Ava Weather Shield	Black
ACC-WEA-SHI-W	Avigilon Ava Weather Shield	White
ACC-CON-BCK-B	Avigilon Ava Conduit Back Box	Black
ACC-CON-BCK-W	Avigilon Ava Conduit Back Box	White
ACC-ADA-PLA-B	Avigilon Ava Adapter Plate	Black
ACC-ADA-PLA-W	Avigilon Ava Adapter Plate	White
ACC-POL-BRA-W	Avigilon Ava Pole Bracket	White
ACC-POL-BRA-B	Avigilon Ava Pole Bracket	Black
ACC-CRN-BRA-W	Avigilon Ava Corner Bracket	White
ACC-CRN-BRA-B	Avigilon Ava Corner Bracket	Black

To learn more, visit:
www.avigilon.com



Motorola Solutions, Inc. 500 West Monroe Street, Chicago, IL 60661 U.S.A. motorolasolutions.com

© 2023, Avigilon Corporation. All rights reserved. MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. 11-2023 [RK04]